



材质: SUS304-WPB

Smax. ...最大压缩量
Fmax. ...最大负载

■精度

项目	弹簧常数	D尺寸公差 (mm)		L尺寸公差 (mm)	
		3~10	13~	5~50	55~
公差	±10%	0 -0.5	0 -0.8	±1.5	±2.5

①类型码	②D	③L	d	压紧长度	Smax.	Fmax. (N)	弹簧常数 (N/mm)
SUW	3	5	0.35	2.8	2	1.96	0.982
		10	0.4	4.8	4	4.84	1.211
		15	0.45	8.3	6	7.58	1.263
		20	0.45	8.3	6	7.52	1.253
		25	0.5	14	8	10.94	1.368
	4	30	0.5	14	8	11.26	1.408
		5	0.4	2.6	2	3.23	1.617
		10	0.45	3.9	4	4.34	1.085
		15	0.5	6	6	7.58	1.263
		20	0.55	9.4	8	10.03	1.254
	5	25	0.6	14.4	10	12.48	1.248
		30	0.6	14.4	10	12.94	1.294
		5	0.45	2.6	2	1.7	0.850
		10	0.5	3.6	4	4.22	1.055
		15	0.6	7.5	6	7.27	1.211
	6	20	0.6	7.5	8	10.37	1.296
		25	0.65	10.7	10	12.62	1.262
		30	0.7	15.4	12	14.75	1.229
		35	0.7	15.4	14	16.73	1.195
	8	5	0.5	2.4	2	1.98	0.988
		10	0.6	4.2	4	5.26	1.315
		15	0.7	7.4	6	8.84	1.473
		20	0.7	7.4	8	11.95	1.494
		25	0.8	13.6	10	15.96	1.596
	10	30	0.8	13.6	12	19.19	1.599
		35	0.85	17.5	14	25.83	1.845
		40	0.9	23.4	16	27.58	1.724
		45	0.9	23.4	18	31.75	1.764
		50	0.9	23.4	18	31.77	1.765
	13	60	1	41	18	30.4	1.689
		70	1	41	24	41.57	1.732
		10	0.75	5.3	4	4.97	1.243
		15	0.75	5.3	6	7.75	1.291
		20	0.9	10.4	8	12.88	1.610
	16	25	0.9	10.4	10	16.66	1.666
		30	1	17	12	19.37	1.614
		35	1	17	14	22.81	1.629
		40	1	17	16	25.54	1.596
		45	1.1	25.3	18	32.45	1.803
	20	50	1.1	25.3	20	35.94	1.797
		60	1.1	25.3	24	43.22	1.801
		70	1.2	39.6	28	51.63	1.844
SUW	10	10	0.85	5.1	4	5.29	1.323
		15	0.85	5.1	6	8.03	1.339
		20	1	9.5	8	12.24	1.530
		25	1	9.5	10	14.81	1.481
		30	1.1	14.3	12	18.54	1.545
	13	35	1.1	14.3	14	21.7	1.550
		40	1.2	11.4	16	53.84	3.365
		45	1.2	11.4	18	60.61	3.367
		50	1.2	11.4	20	66.68	3.334
		60	1.3	29.9	24	42.84	1.785
	16	70	1.4	43.4	24	41.76	1.740
		15	1	5.75	6	6.94	1.157
		20	1.2	10.5	8	12.11	1.514
		25	1.2	10.5	10	15.14	1.514
		30	1.3	15	12	18.58	1.548
	20	35	1.3	15	14	21.73	1.552
		40	1.4	20.3	16	25.73	1.608
		45	1.4	20.3	18	29.11	1.617
		50	1.5	27.8	20	33.92	1.696
		60	1.5	27.8	24	42.07	1.753
	25	70	1.6	38.4	28	46.45	1.659
		80	1.6	38.4	32	52.93	1.654
		15	1.2	7.2	6	7.39	1.231
		20	1.3	9.1	8	11.59	1.449
		25	1.3	9.1	10	14.58	1.458
	30	30	1.4	12.3	12	18.19	1.516
		35	1.5	16.5	14	21.81	1.558
		40	1.6	21.6	16	23.78	1.486
		45	1.6	21.6	18	28.62	1.590
		50	1.7	28	20	32.02	1.601
	40	60	1.7	28	24	38.35	1.598
		70	1.8	36	28	45.92	1.640
		80	1.8	36	32	54.91	1.716
		20	1.7	10.6	8	20.1	2.513
		25	1.8	12.6	10	28.25	2.825
	50	30	1.8	12.6	12	33.91	2.826
		35	2	19	14	41.52	2.966
		40	2	19	16	47.57	2.973
		45	2	19	18	53.39	2.966
		50	2.2	27.5	20	65.58	3.279
	60	60	2.2	27.5	24	78.65	3.277
		70	2.3	34.5	28	92.9	3.318
		80	2.4	40.8	32	108.58	3.393

- ①线径d大于1mm (含1mm) 时两端面会做磨削加工。
②压紧长度为参考值。批量不同会有若干偏差。
③使用次数100万次 (理想实验条件下, 不超过最大压缩量)。



订购范例
Order

①类型码	-	②D	-	③L
SUW	-	D3	-	L5

①②③步请在数字前加字母, 比如L5。