




材质: SUS304-WPB



Smax. ...最大压缩量
Fmax. ...最大负载

精度

项目	弹簧常数	D尺寸公差 (mm)		L尺寸公差 (mm)	
		4~10	13~	5~50	55~
公差	±10%	0 -0.5	0 -0.8	±1.5	±2.5

①类型码	②D	③L	d	压紧长度	Smax.	Fmax. (N)	弹簧常数 (N/mm)
SUH	4	5	0.45	2.7	1.5	2.97	1.977
		10	0.5	3.8	3	6.19	2.064
		15	0.6	8.1	4.5	10.57	2.348
		20	0.65	11.7	6	12.76	2.126
		25	0.7	16.8	7.5	19.4	2.586
		30	0.7	16.8	9	20.82	2.313
	5	5	0.55	3.3	1.5	2.76	1.843
		10	0.6	4.65	3	6.19	2.064
		15	0.6	4.65	4.5	9.28	2.062
		20	0.75	11.81	6	16.12	2.686
		25	0.75	11.81	7.5	18.61	2.481
		30	0.8	16	9	22.21	2.468
	6	35	0.85	21.68	10.5	27.51	2.620
		40	0.85	21.68	12	30.46	2.538
		45	0.9	28.8	13.5	33.8	2.504
		5	0.65	3.2	1.5	4.31	2.874
		10	0.7	3.9	3	9.87	3.291
		15	0.85	7.7	4.5	17.86	3.968
	8	20	0.9	9.7	6	29.42	4.904
		25	1	15.5	7.5	40.92	5.456
		30	1	15.5	9	42.98	4.776
		35	1.1	24.8	9.8	49.99	5.101
		40	1.1	24.8	10	50.41	5.041
		45	1.1	24.8	11.3	52.4	4.637
	10	50	1.2	39	10	48.97	4.897
		60	1.2	39	14	74.4	5.314
		70	1.2	39	15	78.44	5.229
		10	0.9	5.3	3	10.81	3.602
		15	0.9	5.3	4.5	16.78	3.729
		20	1.1	11	6	26.75	4.459
	12	25	1.1	11	7.5	33.89	4.519
		30	1.2	15.9	9	44.36	4.929
		35	1.2	15.9	10.5	50.32	4.792
		40	1.3	23.1	12	61.51	5.126
		45	1.3	23.1	13.5	68.03	5.039
		50	1.4	33.3	15	73.86	4.924
	14	60	1.4	33.3	18	92.12	5.118
		70	1.5	48	19	92.21	4.853

- ①线径d大于1mm (含1mm) 时两端面会做磨削加工。
②压缩长度为参考值。批量不同会有若干偏差。
③使用次数100万次 (理想实验条件下, 不超过最大压缩量)。

①类型码	②D	③L	d	压紧长度	Smax.	Fmax. (N)	弹簧常数 (N/mm)
SUH	10	10	1.1	6.9	3	11.63	3.877
		15	1.1	6.9	4.5	16.16	3.591
		20	1.2	9.3	6	24.7	4.117
		25	1.2	9.3	7.5	31.19	4.159
		30	1.3	12.7	9	42.98	4.775
		35	1.4	17.5	10.5	49.02	4.669
	12	40	1.4	17.5	12	54.53	4.544
		45	1.5	23.8	13.5	66.77	4.946
		50	1.5	23.8	15	75.8	5.053
		60	1.6	32.4	18	95	5.278
		70	1.7	44.2	21	103.07	4.908
	13	15	1.5	9.2	4.5	29.94	6.654
		20	1.5	9.2	6	36.61	6.102
		25	1.5	9.2	7.5	48.83	6.511
		30	1.8	18	9	69.27	7.697
		35	1.8	18	10.5	75.56	7.196
		40	1.8	18	12	90.68	7.557
	16	45	1.8	18	13.5	100.01	7.408
		50	2	28.5	15	119.4	7.960
		60	2.1	36	18	141.32	7.851
		70	2.2	45.1	21	136.04	6.478
		80	2.2	45.1	20	147.82	7.391
	18	15	1.7	9.6	4.6	28.91	6.284
		20	1.9	14	6	41.05	6.842
		25	1.9	14	7.5	50.9	6.787
		30	1.9	14	9	61.37	6.819
		35	1.9	14	10.5	69.36	6.606
		40	2.2	25.1	12	85.1	7.092
	20	45	2.2	25.1	13.5	92.83	6.876
		50	2.2	25.1	15	106.22	7.081
		60	2.3	30.5	18	148.09	8.227
		70	2.5	44.7	21	167.79	7.990
		80	2.5	44.7	24	195.62	8.151
	22	25	2.3	13.8	7.5	88.61	11.814
		30	2.3	13.8	9	90.78	10.087
		35	2.5	18.8	10.5	102.33	9.746
		40	2.5	18.8	12	115.1	9.592
		45	2.8	29.4	13.5	133.96	9.923
		50	2.8	29.4	15	137.57	9.171
	24	60	3	40.5	18	188.98	10.499
		70	3	40.5	21	217.04	10.335
		80	3.2	54.4	24	286.63	11.943



订购范例
Order

①类型码	-	②D	-	③L
SUH	-	D4	-	L5

③②③步请在数字前加字母, 比如L5。