




材质: SUS304-WPB



②Smax. ...最大压缩量
Fmax. ...最大负载

精度

项目	弹簧常数	D尺寸公差 (mm)		L尺寸公差 (mm)	
		4~10	12~	5~50	55~
公差	±10%	0 -0.5	0 -0.8	±1.5	±2.5

①类型码	②D	③L	d	压紧长度	Smax.	Fmax. (N)	弹簧常数 (N/mm)
SUG	4	5	0.55	3.3	1.25	4.96	3.968
		10	0.65	7	2.5	11.33	4.532
		15	0.7	10.3	3.75	16.53	4.409
		20	0.75	14.4	5	23.69	4.737
		25	0.8	19.4	5	21.3	4.260
	5	5	0.6	2.9	1.25	4.8	3.842
		10	0.75	6.9	2.5	10.39	4.157
		15	0.8	9.8	3.75	15.43	4.115
		20	0.85	13.4	5	21.18	4.236
		25	0.9	17.8	6.25	25.28	4.045
	6	30	0.9	21.8	7.5	26.55	3.540
		5	0.8	3.6	1.25	10.14	8.108
		10	0.9	6.8	2.5	17.31	6.924
		15	1	10.5	3.75	28.33	7.554
		20	1.1	14.6	5	41.99	8.397
		25	1.1	17.9	6.25	42.96	6.873
		30	1.2	23.1	6	52.27	8.711
		35	1.2	27.3	7	51.13	7.304
		40	1.2	31.2	8	51.83	6.479
		45	1.3	34.8	9	84.04	9.338
	8	50	1.3	38.4	10	80.85	8.085
		60	1.3	44.2	9	63.65	7.072
		70	1.4	58.5	10.5	86.68	8.255
		10	1.1	6.9	2.5	19.04	7.616
		15	1.2	9.9	3.75	30.83	8.222
		20	1.3	14	5	41.85	8.370
		25	1.3	14.5	6.25	51.6	8.256
		30	1.4	21.4	7.5	59.86	7.981
		35	1.4	22	8.75	70.16	8.018
		40	1.5	28.9	10	81.15	8.115
		45	1.5	32.6	11.25	85.55	7.604
	10	10	1.3	7.2	2.5	24.12	9.646
		15	1.4	10.2	3.75	34.49	9.198
		20	1.5	13.9	5	45.28	9.055
		25	1.5	16.1	6.25	51.96	8.314
		30	1.6	20.4	7.5	66.83	8.910
		35	1.6	22.8	8.75	61.28	7.003
		40	1.7	27.2	10	79.61	7.961
		45	1.7	30.6	11.25	79.48	7.065
		50	1.8	36.5	12.5	94.31	7.545
		60	1.8	41.4	15	114.56	7.637
		70	1.9	50.8	17.5	140.18	8.010

- ②线径d大于1mm (含1mm) 时两端面会做磨削加工。
③压缩长度为参考值。批量不同会有若干偏差。
④使用次数100万次 (理想实验条件下, 不超过最大压缩量)。

①类型码	②D	③L	d	压紧长度	Smax.	Fmax. (N)	弹簧常数 (N/mm)
SUG	12	15	1.5	9.4	3.75	31.13	8.300
		20	1.6	12.4	5	40.1	8.020
		25	1.7	16.2	6.25	49.28	7.884
		30	1.8	20.3	7.5	61.76	8.235
		40	1.9	28	10	83.35	8.335
		50	2	35.5	12.5	104.76	8.381
		60	2.1	43.6	15	125.42	8.361
		70	2.1	48.8	17.5	113.24	6.471
		80	2.2	58.5	20	142.84	7.142
	13	15	1.8	9.5	3.75	64.22	17.126
		20	1.9	12.9	5	66.06	13.211
		25	2	17	6.25	83.44	13.350
		30	2.1	20.5	7.5	116.15	15.487
		40	2.3	28.2	10	141.92	14.192
		45	2.3	32.2	11.25	163.67	14.548
		50	2.4	36	12.5	187.7	15.016
		60	2.5	44.4	12	191.15	15.929
	14	70	2.6	54	14	230.3	16.450
		15	1.9	10	3.75	56.39	15.036
		20	2	13.5	5	76.37	15.273
		25	2.1	16.3	6.25	87.14	13.943
		30	2.3	21.3	7.5	117.56	15.675
		35	2.3	24.7	8.75	144.37	16.499
		40	2.4	28.2	10	171.72	17.172
		60	2.6	43.6	15	249.8	16.653
	16	80	2.7	61.4	16	215.79	13.487
		15	2	10	3.75	54.54	14.544
		20	2.1	12.1	5	72.22	14.444
		25	2.3	17.3	6.25	84.24	13.478
		30	2.4	21	7.5	110.78	14.771
		35	2.5	24.4	8.75	144.83	16.552
		40	2.6	28	10	182.01	18.201
		45	2.7	31.7	11.25	171.08	15.207
	20	50	2.7	35.8	12.5	162.7	13.016
		60	2.9	43.5	15	341.9	22.793
		70	2.9	49.4	17.5	235.9	13.480
		80	3	59.3	16	236.34	14.771
		25	2.9	16.7	6.25	184.81	29.569
		30	3	20.3	7.5	196.02	26.136
		35	3	22.7	8.75	175.74	20.084
		40	3.2	27.2	10	229.52	22.952
		45	3.2	29.6	9	171.99	19.110
		50	3.4	38.3	10	223.96	22.396
		60	3.5	44.6	12	326.82	27.235



订购范例
Order

①类型码	-	②D	-	③L
SUG	-	D4	-	L5

②③步请在数字前加字母, 比如L5。